

LEGEND	
	SURFACE MOUNTED LIGHT FIXTURE
	RECESS LIGHT FIXTURE
	WALL MOUNTED WALL SCONCE
	EXTERIOR WALL MOUNTED LIGHT FIXTURE
	RECESSED LIGHT FIXTURE WATERPROOF IN SHOWER
	HEAT LAMP
	WALL MOUNTED LIGHT FIXTURE
	UNDER CABINET TASK LIGHT FIXTURE
	SURFACE MOUNTED FLUORESCENT WALL SCONCE
	SURFACE MOUNTED FLUORESCENT WALL SCONCE
	1'x4' OR 2'x4' SURFACE MOUNTED LIGHT FIXTURE ON GYPSUM BOARD CEILING
	2'x2' LIGHT FIXTURE IN LAY-IN CEILING
	2'x4' LIGHT FIXTURE IN LAY-IN CEILING
	2' X 4' LAY-IN ACOUSTICAL SUSPENDED CEILING (SCORED 2' X 2') SEE SPECS FOR PANEL TYPES
	GYPSUM BOARD CEILING
	D.A.F.S. SOFFIT
	AIR SUPPLY DIFFUSERS
	AIR RETURN / EXHAUST GRILLES
	LINEAR AIR SUPPLY/RETURN DIFFUSER

GENERAL NOTES:

- REFER TO SPECIFICATIONS FOR INFORMATION ON EACH CEILING TYPE.
- TYPICAL CEILING ELEVATION SHALL BE 8'-0" A.F.F. U.O.N.
- REFER TO ELECTRICAL DRAWINGS AND SPECIFICATIONS FOR ADDITIONAL LIGHTING INFORMATION.
- DUCTWORK IS DIAGRAMMATIC ONLY - REFER TO MECH. DWG'S FOR ROUTING AND SIZING.
- ALL GYPSUM BOARD DROPS TO BE 1'-6" WIDE UNLESS OTHERWISE NOTED.



REFLECTED CEILING PLAN
scale: 3/16" = 1'-0"